



Paddington Sports



Finished Size Approximately: 72" X 90"

www.QuiltingTreasures.com

© Paddington & Co. 2010



Paddington Sports



21324 GB



21325 E



21326 B



21327 B



21327 R



21328 H



21329 B



21329 R



21329 H



21329 S



21323 S



21325 E (backing)

Yardage Requirements

Pattern Yards

21323 S 1 PANEL

21324 GB 2¼

21325 E 6
(inc backing)

21326 B ¾

21327 B 1

21327 R 1

21328 H 1

21329 B 1¾

21329 R ½

21329 H ½

21329 S ½





Paddington's Sports

By Peggy Smith Welchert

Quilt Size: 72" x 90" Skill level: Advanced

*Note: Unless noted, measurements are given in inches and seam allowance is 1/4". Strips are cut selvedge to selvedge. WST= wrong sides together
RST = right sides together*

Materials Needed:

One Book Panel 21323-S

2 1/4 yards 21324-GB

1/2 yard 21325-E

3/8 yard 21326-B

1 yard 21327-B

1 yard 21327-R

1 yard 21328-H

1 3/4 yards 21329-B

1/2 yard 21329-R

1/2 yard 21329-H

1/2 yard 21329-S

5 1/2 yards backing fabric

CUTTING AND FABRIC PREPARATION:

1. Panel 21323-S: Cut 1/4" beyond all edges of each picture creating (12) 7 1/2" squares and (2) 17 1/2" x 8 1/2" rectangles.
2. 21324-GB: Cut (2) strips 72 1/2" long, and (4) strips 18 1/2" long. Cut strips 1/4" above the soccer border and 1/4" below the football border including the Paddington playing football border; strips should measure 6 3/4" wide.
3. 21325-E Cut (1) 14" square
4. 21326-B Cut (1) 9 7/8" strip. Sub-cut (4) 9 7/8" squares. Cut (2) of the squares in half diagonally to create 4 triangles.
5. 21327-B Cut (3) 10 1/4" strips. Sub-cut into (10) 10 1/4" squares.
6. 21327-R Cut (3) 10 1/4" strips. Sub-cut into (10) 10 1/4" squares.
7. 21328-H a. Cut (2) 9 7/8" squares. b. Cut (12) 1 7/8" strips.
8. 21329-B a. Cut (2) 5 3/4" strips. Sub-cut into (12) 5 3/4" squares. b. Cut (1) 7 1/2" strip. Sub-cut into (24) 1 1/2" x 7 1/2" pieces. c. Cut (1) 9 1/2" strip. Sub-cut into (24) 1 1/2" x 9 1/2" pieces and (4) 1 1/8" x 9 1/2" pieces. d. Cut (1) 1 1/2" strip. Sub-cut into (2) 1 1/2" x 17 1/2" pieces. e. Cut (8) 2 1/4" strips.
9. 21329-R Cut (2) 5 3/4" strips. Sub-cut into (12) 5 3/4" squares.
10. 21329-H Cut (4) 3 1/8" strips. Sub-cut into (48) 3 1/8" squares.
11. 21329-S Cut (4) 3 1/8" strips. Sub-cut into (48) 3 1/8" squares.

PIECING:

12. Mark a diagonal line, corner to corner, on the wrong side of all 21329-H 3 1/8" squares with a fine pencil. Place 2 marked squares right side down onto the right side of a 21329 R 5 3/4" square with the marked lines going from corner to corner diagonal. (Figure 1) Sew 1/4" on both sides of the marked lines. Cut on the marked lines and press towards darker fabric. Repeat with all the remaining 21329 R 5 3/4" squares.

13. Using the remaining 21329-H 3 1/8" squares, place squares RST with the diagonal line going from corner to the middle of the triangle. (Figure 2) Sew 1/4" away on both sides of the marked lines. Cut on the marked lines and press towards darker fabric. Repeat with all the remaining 21329-H 3 1/8" squares. Cut on the marked lines and press towards darker fabric to create 48 flying geese. (Figure 3)



Fig. 1

Fig. 2

Fig. 3

14. Sew 4 flying geese together, all facing the same direction, to form a unit that is 4 1/2" by 9 1/2".
15. Repeat Steps 12 to 14 above with 21329-S 3 1/8" squares and 21329-B 5 3/4" squares. Sew together one unit from above to one unit just made with the points going opposite directions to create a 9 1/2" square; repeat to make a total of 12 blocks. All blocks must look the same.
16. Sew one 21329-B 1 1/2" x 7 1/2" rectangle to left and right side of all 12 Paddington Sports 7 1/2" blocks cut from 21323-S. Press towards dark. Sew one 1 1/2" x 9 1/2" rectangle to top and bottom of each unit just created. Press to dark.
17. Mark a diagonal line corner to corner on the wrong side of both of the 21326-B 9 7/8" squares. Place one square RST with a 21328-H 9 7/8" square, matching edges. Sew 1/4" away on both sides of the marked line. (Figure 4) Cut on line. Press seam towards Paddington head print. Repeat with remaining squares, for a total of (8) half-square triangles.



18. Mark a diagonal line corner to corner on the wrong side of each 21327-R 10 ¼" squares. Place one square RST with a 21327-B 10 ¼" square, matching edges. Sew ¼" away on both sides of the marked line. Cut on line. Press to the darker fabric. Mark a line diagonally corner to corner through opposite colors on one unit. Place unmarked unit and marked unit RST with opposite colors together. Sew ¼" away on both sides of the marked line. Cut on marked line. (Figure 5) Press seam to the darker fabric. Repeat with remaining squares.



Fig. 4




Fig. 5

19. Fold 21326-B triangles RST and finger press to mark the center on the cut edge. Fold the 14" square 21325-E in half WST, finger pressing to mark the center along the cut edges; fold in half WST the other direction and again finger press to mark the center along the cut edges. Match up the finger pressed center marks, and sew one triangle of 21326-B on opposite sides of 14" square 21325-E. Press seam towards triangle. Sew remaining 2 triangles on the other two sides of the square. Press seam. Trim evenly to 18 ½".

20. Sew together six 21328-H 1 ⅞" strips. Press seam open. Sew one unit on top and bottom of each 21324-GB 72 ½" long strip. Using the remaining strips sew on top and bottom of each 21324-GB 18 ½" long strip. Trim to make even and press each seam away from 21328-H.

21. Sew one 21329-B 1 ½" x 17 ½" to the top of the 21323-S sailing unit.

22. Sew one 21329-B 1 ½" x 17 ½" to the bottom of the 21323-S Padding Sport unit.

23. Sew one 21329-B 1 ⅛" x 9 ½" on each side of the units just made.

Quilt Center Assembly:

24. Looking at picture of quilt, assemble all units into rows. The middle row is made up of two rows sewn together first then added to either side of 18 ½" square within a square unit.

25. Sew rows together.

26. Add borders.

FINISH THE QUILT

27. Cut the backing fabric into (2) 2 ¼ yards long pieces.

28. Using a ¼" – ½" seam allowance, sew the two pieces of backing fabric together, along the long side. Press the seam open.

29. Center and lay the batting on top of the wrong side of the backing fabric.

30. Center and lay the pieced quilt top on top of the batting.

31. Pin or baste the quilt sandwich using your preferred method for securing the layers.

32. Quilt as desired.

33. Use the (8) 21329-B 2 ¼" strips to bind the quilt.

While all possible care has been taken to ensure the accuracy of this pattern we cannot be responsible for printing errors to the way in which individual work varies.