

# She Who Sews





Finished Quilt Size: 39" x 58" Designed By: Janet Wecker Frisch




## She Who Sews











23064 EJ

23067 E

23068 J

23070 B (Binding)







(Binding)

23071 R

23066	Ē
23000	$\mathbf{L}$

FABRIC REQUIREMENTS		
Design:	Yards	
23064 EJ	1 PANEL	
23067 E	3/4	
23068 J	1/2	
23070 B *Note: Binding for quilt #2 only	3/4	
23070 S *Note: Inner frame for quilt #1 only	1/2	
23071 R *Note: Binding for quilt #1 only	3/4	
23071 R *Note: Inner frame for quilt #2 only	1/2	
23066 E *This allows for one width as backing. Please adjust if you prefer a larger backing.	13/4	

EARRIC REQUIREMENTS

### **Cutting Directions:**

Note: All strips are cut across the width of the fabric unless noted otherwise.

Quilt #1 uses fabrics A, B, C, E and F. Quilt #2 uses fabrics A, B, C, D and G.

#### A. 23064 EJ: Panel

• Cut panel <sup>1</sup>/<sub>4</sub>" outside of design area.

#### B. 23067 E: Ecru/Black Toile

• Cut (5)  $4\frac{1}{2}$ " strips; subcut two strips  $4\frac{1}{2}$ " x  $34\frac{1}{2}$ ". Sew remaining strips together end to end; press. Cut two strips 4½" x 45½".

#### C. 23068 J: Black/Ecru Girl Pattern Girl Print

• Cut (5)  $2\frac{1}{2}$ " strips; subcut two strips  $2\frac{1}{2}$ " x  $38\frac{1}{2}$ ". Sew remaining strips together end to end; press. Cut two strips 2½" x 53½".

#### D. 23070 B: Blue Tape Measure Print \*Binding for quilt #2

• Cut (5) 4½" strips for binding. Note: Quilt was designed with a wide, decorative binding. If you prefer a traditional width binding, cut (5)  $2\frac{1}{2}$ " strips instead.

#### E. 23070 S: Yellow Tape Measure Print

\*Inner frame for quilt #1

• Cut (4) 3" strips.

#### F. 23071 R: Red Pincushion Print

\*Binding for quilt #1

• Cut (5) 4½" strips for binding. Note: Quilt was designed with a wide, decorative binding. If you prefer a traditional width binding, cut (5)  $2\frac{1}{2}$ " strips instead.

#### G. 23071 R: Red Pincushion Print

\*Inner fame for quilt #2

• Cut (4) 3" strips.

#### **Quilt Construction:**

- 1. Center one inner frame strip (E or G) to center of one side of panel. Sew and press toward frame strips. Repeat for opposite side of panel.
- 2. Center one inner frame strip to center of both top and bottom of panel. Sew and press toward frame strips.
- **3.** Trim framed panel to  $26\frac{1}{2}$ " x  $45\frac{1}{2}$ ".



## She Who Sews



- **4.** Sew one 4½" x 45½" [B]toile strip to both sides of quilt. Sew one 4½" x 34½" [B] toile strip to top and bottom of quilt. Press toward toile strips.
- **5.** Sew one  $2\frac{1}{2}$ " x  $53\frac{1}{2}$ " [C] black strip to both sides of quilt. Sew one  $2\frac{1}{2}$ " x  $38\frac{1}{2}$ " [C] black strip to top and bottom of quilt. Press toward black strips.

#### Finishing:

- Prepare backing if using more than a single width of fabric.
- 2. Layer quilt top, batting and backing. Quilt as desired.
- **3.** Prepare binding using 4½" strips of [D] or [F]: Sew strips together end to end with diagonal seams; press seams open. Press binding strip in half with wrong sides together. Sew to quilt using a ¾" seam allowance. Proceed to finish binding with your preferred method.